```xml
<?xml version="1.0" encoding='us-ascii'?>
<!ELEMENT xml_Gridstat ANY>

<!-- Specifies the location of the namingservice. -->
<!ELEMENT namingService EMPTY>
<!ATTLIST namingService
      host            CDATA           #REQUIRED
      port            CDATA           #REQUIRED
>

<!-- Information about the (Leaf) QoS Broker itslef (who I am I). -->
<!ELEMENT myInfo EMPTY>
<!ATTLIST myInfo
      myname          CDATA           #REQUIRED
      parentname      CDATA           #REQUIRED
      coordinateX     CDATA           "100"
      coordinateY     CDATA           "100"
>

<!-- Information about (Edge) Status Routers in a cloud. -->
<!ELEMENT vertexTbl (vertex*)>
<!ELEMENT vertex EMPTY>
<!ATTLIST vertex
      name            CDATA           #REQUIRED
      type            (0 | 1 | 2 | 3) "0"
      coordinateX     CDATA           "100"
      coordinateY     CDATA           "100"
      msgPerSec       CDATA           #REQUIRED
>

<!-- Information about the event channels in a cloud. -->
<!ELEMENT edgeTbl (edge*)>
<!ELEMENT edge EMPTY>
<!ATTLIST edge
      srcName         CDATA           #REQUIRED
      srcAdr          CDATA           #REQUIRED
      srcPort         CDATA           #REQUIRED
      dstName         CDATA           #REQUIRED
      dstAdr          CDATA           #REQUIRED
      dstPort         CDATA           #REQUIRED
      type            (0 | 1 | 2) "0"
      bandwidth       CDATA           #REQUIRED
      latency         CDATA           #REQUIRED
>

<!-- Information about this QoS Brokers children. -->
<!ELEMENT childNodeTbl (child*)>
<!ELEMENT child EMPTY>
<!ATTLIST child
      name            CDATA           #REQUIRED
      type            (4 | 5)         "4"
>
```