Chapter 4: Network Layer

Chapter goals:

- understand principles behind network layer services:
  - routing (path selection)
  - dealing with scale
  - how a router works
  - advanced topics: multicast
- instantiation and implementation in the Internet

Overview:


- network layer services
- routing principles: path selection
- IP
  - Addressing
  - Routing
- Internet routing protocols
  - intra-domain
  - inter-domain
- what's inside a router?
- multicast routing

Network layer functions

- transport packet from sending to receiving hosts
- network layer protocols in *every* host, router

three important functions:

- *path determination:* route taken by packets from source to dest. *Routing algorithms*
- *switching:* move packets from router's input to appropriate router output
- *call setup:* some network architectures require router call setup along path before data flows



Network service model

Q: What *service model* for "channel" transporting packets from sender to receiver?

service abstraction

- guaranteed bandwidth?
- preservation of inter-packet timing (no jitter)?
- loss-free delivery?
- in-order delivery?
- congestion feedback to sender?

The most important distinction at the network layer:

virtual circuit
or
datagram?

Virtual circuits


"source-to-dest path behaves much like telephone circuit"

- performance-wise
- network actions along source-to-dest path

- call setup, teardown for each call *before* data can flow
- each packet carries VC identifier (not destination host ID)
- *every* router on source-dest path s maintains "state" for each passing connection
  - transport-layer connection only involved two end systems
- link, router resources (bandwidth, buffers) may be *allocated* to VC
  - to get circuit-like performance


Virtual circuits: signaling protocols

- used to setup, maintain teardown VC
- used in ATM, frame-relay, X.25
- not used in today's Internet



Datagram networks: the Internet model

- no call setup at network layer
- routers: no state about end-to-end connections
  - no network-level concept of "connection"
- packets typically routed using destination host ID
  - packets between same source-dest pair may take different paths



Network layer service models:

Network Architecture	Service Model	Guarantees ?				Congestion feedback
		Bandwidth	Loss	Order	Timing	
Internet	best effort	none	no	no	no	no (inferred via loss)
ATM	CBR	constant rate	yes	yes	yes	no congestion
ATM	VBR	guaranteed rate	yes	yes	yes	no congestion
ATM	ABR	guaranteed minimum	no	yes	no	yes
ATM	UBR	none	no	yes	no	no

- Internet model being extended: Intserv, Diffserv
  - Chapter 6

Datagram or VC network: why?

Internet

- data exchange among computers
  - "elastic" service, no strict timing req.
- "smart" end systems (computers)
  - can adapt, perform control, error recovery
  - simple inside network, complexity at "edge"
- many link types
  - different characteristics
  - uniform service difficult

ATM

- evolved from telephony
- human conversation:
  - strict timing, reliability requirements
  - need for guaranteed service
- "dumb" end systems
  - telephones
  - complexity inside network